

keep a **SharpEye™** on your safety



40/40M

Multi IR Flame Detector

Superior performance, reliability and immunity to false alarms



SharpEye™

The new 40/40M Multi IR Flame Detector is specifically designed for detection of hydrocarbon and hydrogen flames. It detects hydrocarbon-based fuel and gas fires at long distances with the highest immunity to false alarms. The 40/40M can detect a gasoline pan fire at 215 ft (65m) or a hydrogen flame at 100 ft (30m) in less than 5 seconds.

The 40/40M is the most durable and weather resistant flame detector currently on the market. Its new features include a heated window, to eliminate condensation and icing; HART capabilities, for digital communications; lower power requirements, and a compact, lighter design.

Due to increased reliability, the 40/40 Series warranty period has been extended to 5 years and is SIL2 (TUV) approved to IEC 61508.

FEATURES & BENEFITS

- Multi Spectrum Design - for long distance detection of hydrocarbons and hydrogen flames
- High false alarm immunity
- Sensitivity Selection - to ensure no zone crossover detection
- Automatic and Manual Built-In-Test (BIT) - to assure continued reliable operation
- Heated window - for operation in harsh weather conditions (snow, ice, condensation)
- Multiple output options for maximum flexibility and compatibility
 - Relays (3) for Alarm, Fault and Auxiliary
 - 0-20mA (stepped)
 - HART Protocol for maintenance and asset management
 - RS-485, Modbus Compatible
- High Reliability - MTBF - minimum 150,000 hours
- Approved to Safety Integrity Level 2 (SIL2 - TUV)
- 5-Year Warranty
- User Programmable via HART or RS-485
- Ex approved for Zone 1 hazardous area location
 - ATEX
 - IECEx
 - FM/FMC
 - CSA
- 3rd party Performance Tested
 - EN54-10 (LPCB)
 - FM3260 (FM)

APPLICATIONS

Offshore Oil & Gas installations
Onshore Oil & Gas installations and pipelines
Chemical plants
Petrochemicals plants
Storage Tank farms
Aircraft hangars
Power Generation facilities
Pharmaceutical Industry
Printing Industry
Warehouses

Automotive Industry
Explosives & Munitions
Waste Disposal facilities
Hydrogen Fuel Cell Industry
Hydrogen Vehicle Parking & Refueling
Battery Charging areas
Refinery Hydrogenation
Space Industry hydroxyl propellant
Static Fuel Cell systems

keep a SharpEye™ on your safety

GENERAL SPECIFICATIONS

Spectral Response	Multi IR Bands					
Detection Range (at highest Sensitivity Setting for 1ft ² (0.1m ²) pan fire)	Fuel	ft / m	Fuel	ft / m	Fuel	ft / m
	n-Heptane	215 / 65	Ethanol 95%	135 / 40	LPG *	100 / 30
	Gasoline	215 / 65	Methanol	115 / 35	Polypropylene Pellets	16 / 5
	Diesel Fuel	150 / 45	IPA (Isopropyl Alcohol)	135 / 40	Office Paper	33 / 10
	JP5	150 / 45	Hydrogen*	100 / 30	* 20" (0.5m) high, 8" (0.2m) width plume fire	
	Kerosene	150 / 45	Methane*	100 / 30		
Response Time	Typically 5 seconds					
Adjustable Time Delay	Up to 30 seconds					
Sensitivity Ranges	4 Sensitive ranges for 1 ft ² (0.1m ²) n-heptane pan fire from 50 ft (15m) to 215 ft (65m)					
Field of View	Horizontal 67°, Vertical 70° for Gasoline Horizontal 80°, Vertical 80° for Hydrogen					
Built-in-Test (BIT)	Automatic (and Manual)					
Temperature Range	Operating:	-67°F to +167°F		(-55°C to +75°C)		
	Option:	-67°F to +185°F		(-55°C to +85°C)		
	Storage:	-67°F to +185°F		(-55°C to +85°C)		
Humidity	Up to 95% non-condensing - withstands up to 100% RH for short periods					
Heated Optics	To eliminate condensation and icing on the window					

ELECTRICAL SPECIFICATIONS

Operating Voltage	24 VDC nominal (18-32 VDC)					
Power Consumption	Standby:	Max. 90mA (110mA with heated window)				
	Alarm:	Max. 130mA (160mA with heated window)				
Cable Entries	2 x 3/4" - 14NPT conduits or 2 x M25 x 1.5 mm ISO					
Wiring	12 - 22AWG (2.5mm ² - 0.3mm ²)					
Electrical Input Protection	According to MIL-STD-1275B					
Electromagnetic Compatibility	EMI/RFI protected to EN61326-3 and EN61000-6-3					
Electrical Interface	The detector includes twelve (12) terminals with five (5) wiring options (factory set)					

OUTPUTS

Relays	Alarm, Fault and Auxiliary SPST volt-free contacts rated 5A at 30 VDC or 250 VAC.					
0-20mA (stepped)	Sink (source option) configuration					
	Fault:	0 +1mA	Warning:	16mA ± 5%		
	BIT Fault:	2mA ± 10%	Alarm:	20mA ± 5%		
	Normal:	4mA ± 10%	Resistance Loop:	100-600 Ω		
HART Protocol	Optional HART communications on the 0-20mA analog current (FSK) - used for maintenance, configuration changes and asset management, available in mA source output wiring options					
RS-485	RS-485 Modbus compatible communication link that can be used in computer controlled installations					

MECHANICAL SPECIFICATIONS

Materials	- Stainless Steel 316L with electro polish finish					
Enclosure options	- Heavy duty copper free aluminum (less than 1%), red epoxy enamel finish					
Mounting	Stainless Steel 316L with electro polish finish					
Dimensions	Detector	4" x 4.6" x 6.18" (101.6 x 117 x 157 mm)				
Weight	Detector (St.St.)	6.1 lb (2.8 kg)				
	Detector, aluminum	2.8 lb (1.3 kg)				
	Tilt mount	2.2 lb (1.0 kg)				
Environmental Standards	Meets MIL-STD-810C for Humidity, Salt & Fog, Vibration, Mechanical Shock, High Temp, Low Temp					
Water and Dust	IP66 and IP67 per EN60529, NEMA 250 6P					

APPROVALS

Hazardous Area	ATEX and IECEx	Ex II 2 GD, Ex de IIB+H2 T5 (-55°C to + 75°C) Ex tD A21 IP66/X7 T 95°C	Ex de IIB+H2 T4 (-55°C to + 85°C) Ex tD A21 IP66/X7 T 105°C
	FM/FMC/CSA	Class I Div. 1, Groups B, C & D Class II/III Div. 1, Groups E, F & G	
Performance	EN54-10 (LPCB) FM-3260 (FM)		
Reliability	IEC61508 - SIL2 (TUV)		

ACCESSORIES

Fire Simulator	20/20-313	Weather Protector	777163	Mini Laptop Kit	777820	Laser Pointer	777166
Tilt Mount	40/40-001	Air Shield	777161	USB RS485 Harness Kit	794079-5	(Detector area coverage)	